

COMMISSION OF EUROPEAN COMMUNITIES

# AFORISM

A COMPREHENSIVE FORECASTING SYSTEM  
FOR FLOOD RISK MITIGATION AND CONTROL

Contribution of the National Technical University of Athens  
to the 2<sup>nd</sup> annual progress report

Th. Xanthopoulos, D. Koutsoyiannis and I. Nalbantis

September 1993

Research Contract no.: EPOC-CT90-0023



Contract no.: EPOC-CT90-0023

Contractor Institution: NTUA-DWR, National Technical University of Athens

Project leader: Prof. Themistocle S. XANTHOPOULOS

Other institutions co-operating: University of Bologna  
Ente Regionale di Sviluppo Agricolo  
University College Cork  
University of Newcastle Upon Tyne  
Ecole Polytechnique Federale de Lausanne  
Instituto Superior de Agronomia, Lisbon  
Institut National Polytechnique de Grenoble

Starting date: June 1<sup>st</sup>, 1991

---

Title of the project: A comprehensive Forecasting system for flood RISk  
Mitigation and control (AFORISM)

---

## 1. OBJECTIVES

The research of NTUA-DWR has two basic lines within the framework of AFORISM: the study of intense, flood producing, rainfall and the study of rainfall-runoff models.

The study of intense rainfall includes:

- (a) analysis and modelling of the temporal structure of storm events at a point and areal (lumped) basis,
- (b) construction of a stochastic rainfall generator by using disaggregation techniques, and
- (c) application of the rainfall generator for generation of storm scenarios and testing of the model results.

The second line of research includes:

- (a) evaluation of the performance of several rainfall-runoff models with emphasis on their runoff production part by treating the transfer to the watershed's outlet in a uniform way,
- (b) addressing the problem of data inadequacy that arises from the gauging networks with non-recording devices; a methodology for integrating, in a continuous-time model, information from both daily and shorter time-step data is sought,
- (c) investigation of the usefulness of the FDTF-ERUHDIT method in tackling the above problem described in b,
- (d) examining the possibility of initialising continuous-time rainfall-runoff models through models of the same structure operating on a daily time basis, and
- (e) participation in testing of different rainfall-runoff models with the framework of the common experiment of the project.

## **2. METHODS, DATA AND MATERIALS**

### **2.1 Methods**

Modern techniques, based on the theory of self-similar (scaling) processes are used for modelling of the time distribution of rainfall. In addition, the meteorological conditions of the area are considered in order to classify storm events by weather type. New disaggregation techniques with simple structure and reduced parameter sets, which can be combined with the stochastic rainfall model are developed.

For rainfall-runoff modelling two well-known conceptual rainfall-runoff models were applied. An analysis framework for model testing was set up to perform different model calibrations of the same model on different kinds of data and to link model operation on more than one time steps.

### **2.2 Hydrologic data**

The Evinos River basin, Middle Greece, at Poros Righaniou with a total area of 884 km<sup>2</sup> was selected as the study area. A database was constructed for the rainfall and runoff data for that basin. For the rainfall model development and parameter estimation the data of three recording rain gauges for a 20 year period were digitised on an hourly time basis. In addition, weather maps at the surface and 500 mb level for the same period were used. Some 500 intense rainfall events were isolated from the time series by using certain criteria for event identification and selection. For the first period of rainfall model testing a data set of the Aliakmon River basin, province of Macedonia, Greece was also used.

For rainfall-runoff modelling, the following data of the Evinos River basin were obtained:

- (a) Hourly rainfall data of three rain recorders for a 20-year period.
- (b) Daily rainfall of six rain gauges for an about 30-year period.
- (c) Hourly runoff data at the outlet for 28 flood events.
- (d) Hourly runoff data at the outlet and maximum and minimum daily temperatures for a 2-year period.
- (e) Daily runoff at the outlet for a 8-year period.
- (f) Daily mean temperature of 3 measuring stations, for a 8-year period (as in e).

### **2.3 Materials**

The FDTF-ERUHDIT identification package was obtained from French EDF within the frame of collaboration with the French partner. Initial FORTRAN code of the TANK model was provided by UNIBO-ICI and served as a basis to recode the model All the developed models have been programmed and run on a PC/DOS environment in Pascal programming language. No other software packages have been used. It is scheduled that part of the rainfall model will

be transferred into a UNIX environment with C programming language on a HP/730 RISC workstation.

### **3. RESULTS TO DATE**

#### **3.1 Rainfall modelling**

For the rainfall analysis and modelling, the data set of intense rainfall events at the Evinos River basin, was analysed. Initially, the rainfall events of both rainy and dry season were classified into different weather types. The specific weather types examined were introduced by Maheras (1982) and their definition depends on weather characteristics such as the location of centres of anticyclones, the main trajectories of cyclones, and some special characteristics at the surface and at the 500 mb level. It was found that two of the weather types, namely the cyclonic types SW1 and NW1 give rise to the majority of intense rainfall events (about 30% each one), while other four cyclonic types (W1, W2, SW2, NW2) and one special type (DOR) produce intense rainfall at a less frequency. The main characteristics of the rainfall events (mean and variance of event duration and of total and hourly depth; lag one autocorrelation coefficient of hourly depth) were calculated for each class of events belonging to a specific weather type. By comparison of different classes it was concluded that, apart from the probability of occurrence of a storm, only few significant differences appear between characteristics of different weather types. Thus, the introduction of weather types does not explain high portion of the variability of rainfall. On the contrary, the differences of the rainfall characteristics between rainy and dry season are statistically significant.

The temporal structure of the rainfall at an event basis was modelled by a self similar (simple scaling) model (Koutsoyiannis and Foufoula, 1993). The model is based on the hypothesis that the rainfall process at any time position in the interior of a storm of a certain duration is a simple scaling process with a constant scaling exponent. Thus, the processes of intensity in two events with different durations are proportional (in distribution) to each other, under appropriate scaling of time determined by the ratio of the durations, with the proportionality ratio being a power of the ratio of durations with exponent equal to the scaling exponent. The consequences of this hypothesis are that the mean and standard deviation of total storm depth increase with duration each according to a power law with the same exponent; also, the mean and standard deviation of the incremental, say hourly, depth increase with duration according to the same power law; the lag-one correlation coefficient of incremental depths increases with duration; and the decay rate of the autocorrelation function of the incremental rainfall depth decreases with duration. At the stage of initial model testing the rainfall data of the Aliakmon River basin were used and it was found that the model is in good agreement with those data. Furthermore, it was found that the scaling model is superior to other simple temporal rainfall models, which were unable to capture important statistical properties of storm rainfall.

The model was subsequently applied to the data of Evinos River basin and calibrated separately for the storms of each of the two seasons (rainy and dry). It was found to fit well to the historical data of both seasons, thus providing a basis for modelling of intense rainfall events. It is remarkable that the fitting is also good for rainfall characteristics that were not used explicitly for the estimation of model parameters. The conclusion is that the scaling rainfall model fits the intense rainfall data in both seasons and thus, can provide a basis for modelling of intense rainfall events.

In addition, an event-based rainfall generation model was developed which embodies two different generation forms: a typical sequential form and a disaggregation form. Both forms of the generation model are compatible and can be combined with either the scaling model or any other appropriate rainfall model and can perform with arbitrary time step less than the duration. The sequential form of the model is based on the generalised matrix relation  $\mathbf{X} = \mathbf{\Omega}\mathbf{V}$  where  $\mathbf{X}$  is the vector of incremental depths inside the event,  $\mathbf{V}$  is a vector of independent variables and  $\mathbf{\Omega}$  is a matrix of coefficients. Given the marginal and joint moments of the incremental depths (e.g., as a consequence of the scaling model) the moments of  $\mathbf{V}$  and the coefficients  $\mathbf{\Omega}$  can be easily determined.

On the other hand, the disaggregation model can divide the total depth of an event with known duration into incremental depths. The disaggregation technique is characterised by simplicity and parsimony of parameters; it assumes a random shape of the hyetograph and it is compatible with various rainfall models. It is well known that most disaggregation models of the literature (e.g., Valencia and Schaake, 1972, 1973; Mejia and Rousselle, 1976; Todini, 1980; Stedinger and Vogel, 1984; Pereira et al., 1984; Lane and Frevert, 1990; Grygier and Stedinger, 1990; Koutsoyiannis, 1992) are not applicable to short scale rainfall disaggregation. Other models such as the one by Koutsoyiannis and Xanthopoulos (1990) are especially designed for short scale rainfall disaggregation but are not so generalized as to be combined with any rainfall model since they include certain hypotheses about the stochastic structure of the rainfall process. The present model is generalized in a high degree since the only hypothesis it uses is that the incremental rainfall depths are approximately gamma distributed and not very highly serially correlated. With this assumption it was found that a simple disaggregation method consisting of two steps, where the first step consists in the application of the above mentioned sequential model and the second is an adjustment procedure, can give good approximations of the important statistics of interest. Furthermore, under some ideal conditions the disaggregation method was shown to be exact in a strict sense, i.e. it preserves the complete distribution of the variables. Both generation techniques were combined with three alternative rainfall models (the scaling model, a Markovian in continuous time and a Markovian in discrete time). The results of the model application and testing at these three cases indicated good approximation of the important statistics of

incremental rainfall depths (first, second and third order marginal moments, marginal distributions, and joint second order statistics).

The generation model was then reformulated such as to form a generation scheme of the future evolution of a storm given the situation at the current time step  $k$  and the previous ones. For this purpose, a conditional simulation scheme with two main steps was used. At the first step the total duration  $D$  is generated from the conditional distribution given that  $D > k$ . The second step involves the generation of the sequence of incremental depths  $X_j$  ( $j = k+1, \dots, D$ ) given the observed depths  $X_1, \dots, X_k$ .

Three different implementations of the conditional simulation model were examined. In the first implementation nothing was presumed about the future of the event except for the condition  $D > k$ , while in the second implementation it was assumed that the duration  $D$  was approximately known from a meteorological prediction with an accuracy of 10%. In both implementations, starting at the situation of the step  $k$ , the complete evolution of the hyetograph till the end of the event was generated. By applying these two implementations and comparing with historical data it was found that the forecasting is poor for both of them, except for an initial time period. The third implementation concerned a forecasting scheme with one-hour lead time, which adapts its conditions every hour given the updated series of hourly depths. By application of this implementation and comparison with historical data it was found that the forecasted hyetographs capture the shape of the observed hyetograph. The main conclusion drawn from this part of the study is that, due to the high coefficient of variation ( $> 1$ ) and the relevantly low autocorrelation function of hourly depths, the stochastic forecasting of the evolution of the rainfall process is impractical. However, an one-hour forecasting by stochastic methods may be feasible.

### **3.2 Rainfall-runoff modelling**

In steep headwater basins with a size ranging from several tens to several hundreds km<sup>2</sup>, as it is very frequently the case in the Mediterranean zone, very short response times (up to a few hours) are encountered. This obliges the modeler of the basin's response to adopt a time step for discretisation of the hydrologic data within the range from a fraction of 1 hour to a few hours. This kind of data necessitates the existence of recording devices such as recording rain gauges, stage recorders and recording temperature gauges. However, during the design phase or even the very early stages of operation of a flood forecasting system a common situation for many catchments consists in the following: (a) a rather dense network of non-recording devices is present providing data for a long period (e.g. 20 or 30 years or more) on a daily basis in the most usual case, (b) there are a few recording devices with short periods of operation providing discontinuous records in most cases related to some water resources study, and (c) a proper network of recording devices is planned to be installed. In such a situation the modeller of the basin faces two alternatives: (a) either use only the limited set of pieces of continuous charts to extract some flood events and then follow an event-based

modelling approach, or (b) use the above charts in combination with the daily data in the hope to embody all available information in a continuous-time model. It is the latter approach that we have chosen to explore within the AFORMISM project.

We limited our analyses in the calibration of continuous-time lumped rainfall-runoff models which are widely used in flood forecasting for small and medium-sized headwater basins. Among the models of this category we have chosen those that have the common structure used in the Unit-Hydrograph modelling context, namely they comprise of one first part called production function and a second part, the transfer function. The first part summarises all hydrologic processes involved in an idealised soil column representative of the whole basin and yields the runoff volume or effective rainfall for each time step. The transfer function encompasses all transfer processes within the catchment and is reasonably assumed linear thus satisfying the assumptions of the Unit Hydrograph. In a recent paper (Duband et al., 1993) a new approach for calibrating lumped rainfall-runoff models, called FDTF-ERUHDIT was presented. Based on the Unit Hydrograph concept, the method performs a simultaneous identification of the effective rainfall series and the First Differenced transfer function or Unit Hydrograph through an alternate iterative procedure without presupposing any runoff production function or applying any arbitrary baseflow removal. The FDTF-ERUHDIT method was a key element in our analyses. We set up a framework for model validation which is then applied to a Greek basin. Two well-known rainfall-runoff models were selected for the analyses, the version of the SACRAMENTO model adopted by the U.S. National Weather Service known as the Soil Moisture Accounting (SMA) of the U.S. National Weather Service River Forecast Service or SMA-NWSRFS (Burnash et al., 1973), and the TANK model (Sugawara et al., 1983).

Our approach consisted in the following:

- (a) For each model structure (e.g. that of the TANK model) calibrate a daily model based the long continuous-time data set that is available.
- (b) Calibrate the transfer function of the model on the time step suitable for the dynamics of the basin which in our case was equal to 1 hour; the calibration is made on the event-based data set available through the FDTF-ERUHDIT method without presupposing any production function.
- (c) Based on the above identified parameters construct a new continuous-time model, called the derived model; its production function parameters are derived from those of the daily model while the parameters of its transfer function are the only ones which are directly identified (as described in b).

The problem is how to perform this transformation of the parameters of the production function from one time step to another. We studied a certain number of cases related to the model structures selected; these cover, to our opinion, a broad spectrum of cases appearing in conceptual rainfall-runoff models commonly used in practice.

The framework for validation of our approach comprised of the following steps:

- (1) Identify, for comparison purposes, a reference model on the continuous-time data set available on a short time basis; of course, this data set is available only in our case study and not in the real-world situation that faces our approach.
- (2) Based on the continuous daily and the event-based data sets obtain the derived model.
- (3) Evaluate and compare the performances of the two models.
- (4) Examine the possibility of initialising the derived model through the daily model; a composite scheme is tested on several flood events: first the daily model is run up to the day before the flood and then the derived model is launched.
- (5) Detect any deficiencies in the composite scheme and propose improvements.

The above framework was applied on the Evinos watershed through an extensive series of tests. The transfer function identified through the FDTF-ERUHDIT method over a length of 20 time steps through 5 iterations is found to have a time-to-peak equal to 6 hours. The overall determination coefficient starts from 0.823 in the first iteration and reaches 0.918 in the 5th iteration; for the 5th iteration it varies from 0.723 to 0.980 for different events.

The performance criteria for model calibration and verification periods were compared for both the daily and the hourly reference models. The results are practically the same for the two model structures as reported by others (see, for example, Franchini and Pacciani, 1990). The daily models were less good than the hourly ones and their performance criteria were lower by 10 to 20% from those of the hourly models. Then, a comparison was made between the derived models and the corresponding reference models. We observed that the performance of the derived model is very close to that of the daily models, that is only 10 to 20% lower than the best (i.e. the reference) models.

To investigate the possibility of initialising the derived model through the daily model we examined the transferability of the values of state variables from the daily to the derived hourly model. This was done by performing a linear regression of the end-of-day values of these states for the two models. For the SMA-NWSRFS model very high values of  $R^2$  (higher than 0.85) were found for all state variables of the lower zone of the model while for the upper zone  $R^2$  took rather poor values. The same result was shown by the regression coefficients  $\alpha$  and  $\beta$ . For the TANK model the results were completely analogous: high values of  $R^2$  for the variables of the lower zone and rather poor values for the upper zone; in the latter zone only the contents of the two sub tanks and were used in the analysis because of the fact that the other variables (the contents of the two free water storages) took values always very close to zero; in fact their depletion coefficients summed practically to unity thus excluding any storage functioning of these elements and in any case a zero value was always a good prediction. Of course, this result is particular to the dynamics of the basin chosen as compared to the time steps used, but it does not pose any problem to the validation of our methodology nor reduces the generality of the approach.

After having been assured that a direct transfer of the states from the daily model to the so called derived model is possible, we tested, for some flood events, a simulation scheme with the daily model providing initial conditions for the derived model; the latter model is activated only in flood periods. Comparisons with the continuous run of the reference model showed that this composite scheme is satisfactory especially if the contents of the upper storage elements are tuned at the moment of shifting from the daily to the derived model.

The main conclusions drawn from our study are:

- (1) It is not an uncommon situation for many countries to dispose inadequate hydrologic data during early stages of design and development of a flood forecasting system; in particular, large amounts of daily data are usually available together with event-based data sets; while the most straightforward approach is to calibrate event-type model, we propose an alternative approach to calibrate a continuous-time rainfall-runoff model integrating both daily and shorter time-scale information
- (2) The calibration procedure recommended utilises the FDTF-ERUHDIT method for Unit Hydrograph identification to estimate the transfer function while the runoff-production function is derived by calibrating the whole model on daily data.
- (3) The resulting derived model performs well in continuous simulation and can be easily initialised through the daily model; the performance of this scheme is very much improved through tuning of the states directly related to the quickflow component of the runoff.
- (4) The methodology for integrating information on different time steps in a continuous-time rainfall-runoff model was validated in a modelling context with noisy data similar to that motivated the whole study; further insight can be expected by making extra tests on generated error-free data; an attempt to do this is planned for the future

## **4. FUTURE WORK**

### **4.1 Rainfall modelling**

The objectives concerning the rainfall modelling are almost fulfilled by the end of the second year. What it remains is the completion of analysis of weather types and the calibration and application of the model in the Reno River basin. After the extension of the project by one year, an attempt will be made for the extension of the model to a multivariate form.

### **4.2 Rainfall-runoff modelling**

We consider that the objectives of the AFORISM project have been attained as far as the implementation and testing of rainfall-runoff models to a Greek basin. As an outcome of this, a methodology for coping with data inadequacy was set up and extensively tested. Within the extension period (third year) of the AFORISM project the models already implemented in a Greek basin will be applied in the Reno River Basin which was chosen for the common experiment of the project

## REFERENCES

- Burnash, R. J. C., Ferral R. L., and McGuire R. A., A generalized streamflow simulation system-conceptual modelling for digital computers, Joint Federal State River Forecasting Center, Sacramento, Calif., 1973.
- Duband, D., Obled, Ch., and Rodriguez, Y., Unit Hydrograph revisited: an alternate iterative approach for U.H. and effective precipitations identification, *J. of Hydrol.*, 1993 (in press)
- Franchini, M., and Pacciani, M., Comparative analysis of several conceptual Rainfall-Runoff models. *J. of Hydrol.*, 70, 1-24, 1993.
- Grygier, J.C. & Stedinger, J.R., SPIGOT, A synthetic streamflow generation software package, Technical description, School of Civil and Environmental Engineering, Cornell University, Ithaca, NY., Version 2.5, 1990.
- Koutsoyiannis, D. and Xanthopoulos, Th., A dynamic model for short-scale rainfall disaggregation, *Hydrol. Sci. J.*, 35(3) 303-322, 1990.
- Koutsoyiannis, D., A nonlinear disaggregation model with a reduced parameter set for simulation of hydrologic series, *Water Resour. Res.*, 28(12), 3175-3191, 1992.
- Koutsoyiannis, D. and Foufoula, E., A scaling model of storm hyetograph, *Water Resour. Res.*, 1993 (in press).
- Lane, W.L. and Frevert, D.K., Applied Stochastic Techniques, User's Manual, Bureau of Reclamation, Engineering and Research Center, Denver, Co., Personal Computer Version 1990.
- Maheras, P., Synoptic situations and multivariate analysis of weather in Thessaloniki (in Greek), Publication of the Laboratory of Climatology, University of Athens, Greece, 1982.
- Mejia, J.M. and Rousselle, J., Disaggregation models in Hydrology revisited, *Water Resour. Res.*, 12(2), 185-186, 1976.
- Sugawara, M., Watanabe, I., Ozaki, E., and Katsuyame, Y., Reference manual for the TANK model, National Research Center for Disaster Prevention, Japan, 1983.
- Todini, E., The preservation of skewness in linear disaggregation schemes, *J. Hydrol.*, 47, 199-214, 1980
- Valencia, D. and Schaake, J.C., Disaggregation processes in Stochastic Hydrology, *Water Resour. Res.*, 9(3) 211-219, 1973.